



OIL & GAS WELL DRILLING, DIESEL SLURRY

Product Id: SA - FHG 35

SA - FHG 35 is a fine white to pale yellow powder having high viscosity, used in oil drilling due to fast hydration. Product Specification ensured by Shreeji Agro is as follows:

Application:

Fast Hydrating Guar Gum Products, Oil & Gas Well Drilling.

Chemical Analysis:

| | |
|-------------|-------------|
| MOISTURE | 10% Maximum |
| ASH | 1% Maximum |
| GUM CONTENT | 80% Minimum |
| pH | 5.5 - 7.5 |

Granulation:

| | |
|------------------|-------------|
| ON 40 mesh | NIL |
| ON 100 mesh | TRACES |
| THROUGH 200 mesh | 95% Maximum |

FANN Viscosity:

VISCOSITY IN 2% KCL SOL. AT FANN 35 VISCOMETER AFTER 3 MINUTES ON 300 RPM AT 25°C (STIRRING AT 1500 RPM FOR TWO & HALF MINUTES IN WARRING BLENDER)

| | |
|------------|----------------|
| 3 Minutes | 35 cps Minimum |
| 5 Minutes | 37 cps Minimum |
| 30 Minutes | 39 cps Minimum |
| 60 Minutes | 40 cps Minimum |

Packing:

25 Kg / 50 LBS, Multiwall Paper Bag with inside Polyliner / Laminated / or 500 Kg / 950 Kg Jumbo Bags or As per Buyer's Requirement.