



OIL & GAS WELL DRILLING, DIESEL SLURRY

Product Id: SA - FHG 45

SA - FHG 45 is a fine white to pale yellow powder having high viscosity, used in oil drilling due to fast hydration. Product Specification ensured by Shreeji Agro is as follows:

Application:

Fast Hydrating Guar Gum Products, Oil & Gas Well Drilling.

Chemical Analysis:

MOISTURE	5% Maximum
ASH	1% Maximum
GUM CONTENT	80% Minimum
pH	5.5 - 7.5

Granulation:

ON 40 mesh	NIL
ON 100 mesh	TRACES
THROUGH 200 mesh	95% Maximum

FANN Viscosity:

VISCOSITY IN 2% KCL SOL. AT FANN 35 VISCOMETER AFTER 3 MINUTES ON 300 RPM AT 25°C (STIRRING AT 1500 RPM FOR TWO & HALF MINUTES IN WARRING BLENDER)

3 Minutes	45 cps Minimum
5 Minutes	47 cps Minimum
30 Minutes	49 cps Minimum
60 Minutes	50 cps Minimum

Packing:

25 Kg / 50 LBS, Multiwall Paper Bag with inside Polyliner / Laminated / or 500 Kg / 950 Kg Jumbo Bags or As per Buyer's Requirement.